



DIN 917

Sechskant-Hutmutter

niedrige Form



Ø	h	s	e	r	t min.	t max.	⊙
3		5,5	6,01				5,5
4	5,5	7	7,66	8	4,16	4,64	7
5	7	8	8,79	10	4,96	5,44	8
6	9	10	11,05	12	6,71	7,29	10
8	12	13	14,38	15	9,21	9,79	13
10	14	16	17,77	20	10,65	11,35	16
12	16	18	20,03	25	13,15	13,85	18
14	18	21	23,35	28	14,65	15,35	21
16	20	24	26,75	30	16,65	17,35	24
18	22	27	29,56	32	18,58	19,42	27
20	25	30	32,95	35	20,58	21,42	30
22	28	34	37,29	35	21,58	22,42	34
24	30	36	39,55	40	23,58	24,42	36
27	32	41	45,2	50	25,58	26,42	41
30	34	46	50,85	60	27,58	28,42	46

Güte
▲ ●
▲ ●
▲ ●
▲ ●
▲ ●
▲ ●
▲ ●
▲ ●
▲ ●
▲ ●
▲ ●
▲ ●
▲ ●
▲ ●

▲ A2 / ● A4 | Alle Maße in mm | Weitere Abmessungen auf Anfrage
 Beispiel Art.-Nr.: 917-2-8 DIN 917 - A2 - M8