


Ähnl. ISO 10511 - **DIN 985** Sechskantmuttern

selbstsichernd mit nichtmetallischem Klemmteil, niedrige Form



d	m	h	s	e	●
M2,5	3,5	2,3	5	5,50	5
M3	2,4	2,4	5,5	6,01	5,5
M4	2,9	2,9	7	7,66	7
M5	3,2	3,2	8	8,79	8
M6	4,0	6,0	10	11,05	10
M8	5,5	8,0	13	14,38	13
M10	6,5	10,0	17	18,90	17
M12	8,0	12,0	19	21,10	19
M14	9,5	14,0	22	24,49	22
M16	10,5	16,0	24	26,75	24
M18	13,0	18,5	27	29,56	27
M20	14,0	20,0	30	32,95	30
M22	15,0	22,0	32	35,03	32
M24	15,0	24,0	36	39,55	36
M27	17,0	27,0	41	45,20	41
M30	19,0	30,0	46	50,85	46
M33	22,0	33,0	50	55,37	50
M36	25,0	36,0	55	60,79	55

Güte	SU
▲●	1000
▲●	1000
▲●	1000
▲●	1000
▲●	500
▲●	200
▲●	100
▲●	100
▲●	100
▲●	50
▲●	50
▲●	50
▲●	25
▲●	25
▲●	25
▲●	25
▲●	25
▲●	25

■ A1 / ▲ A2 / ● A4 | VE: Verkaufseinheit | Alle Maße in mm | Weitere Abmessungen auf Anfrage
Beispiel Art.-Nr.: 985-2-8 DIN 985 - A2 - M8